Section 1: Identification of the Substance/Mixture and the Company/Undertaking

Product Name: Vaporseal HM Plus - Part B / Platform EMS - Part B Product Code: 57-0005-B Continental Products, LTD 1150 East 222nd Street Euclid, OH 44117 USA

Distributor: DARO Flooring Systems USA, LLC 9219 63rd Court East Parrish FL, 34219 USA

Email: info@continentalprod.com Phone: 216-531-0710

Chemtrec: 1-800 - 424 - 9300 Chemtrec Global: 1-703 - 741 - 5970

Section 2: Hazard(s) Identification

GHS Ratings:				
	Oral Toxicity	Acute Tox. 2	Oral>5+<=50mg/kg	
	Skin corrosive	1B	Destruction of dermal tissue: Exposure < 1 hour Observation < 14 days, visible necrosis in at least one animal	
	Eye corrosive	1	Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5	
	Skin sensitizer	1	Skin sensitizer	
	Reproductive toxin	2	Human or animal evidence possibly with other information	
<u>GHS H</u>	<u>azards</u>			
	H314	Causes severe skin	burns and eye damage	
	H317	May cause an allerg	ic skin reaction.	
	H318	Causes serious eye	damage	
	H361	Suspected of damage	ging fertility or the unborn child	
<u>GHS P</u>	recautions			
	P201	Obtain special instructions before use Do not handle until all safety precautions have been read and understood		
	P202			
	P261	Avoid breathing dust/fume/gas/mist/vapours/spray		
	P264	Wash thoroughly after handling.		
	P270	Do not eat, drink or smoke when using this product		
	P272	Contaminated work clothing should not be allowed out of the workplace		
	P280	Wear protective gloves/protective clothing/eye protection/face protection		
	P281	Use personal protective equipment as required		
	P310	Immediately call a POISON CENTER or doctor/physician		
	P321	Specific treatment, see supplemental first aid information.		
	P330	Rinse mouth		
	P362	Take off contaminated clothing and wash before reuse		
	P363	Wash contaminated clothing before reuse		
	P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician		
	P302+P352	IF ON SKIN: Wash with soap and water		
	P305+P351+P338		ontinuously with water for several minutes. Remove contact d easy to do - continue rinsing	
	P308+P313	•	rned: Get medical advice/attention	
	P332+P313	-	rs: Get medical advice/attention	
	P333+P313	If skin irritation or a r	ash occurs: Get medical advice/attention	
	P405	Store locked up		
		-		

Dispose of contents/container in accordance with local/regional/national/international regulations. Manufacturer/supplier or the competent authority to specify whether disposal requirements apply to contents, container or both.

Signal Word: Danger



Unnecessary exposure to any chemical should be avoided. NOTICE--Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after applicable limits. Follow respirator manufacturer's directions for respirator use.

Section 3: Composition/Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
INERT ADDITIVE	INERT ADDITIVE	57.50%
Proprietary material	Proprietary material	27.50%
4-tert-Butylphenol	98-54-4	15.00%

Section 4: First Aid Measures

After Inhalation: Immediately supply fresh air. Keep patient in restful and comfortable position for breathing. If required provide artificial respiration, although this may be dangerous. Consult doctor if symptoms persist. **After Eye Contact:** Immediately rinse opened eye(s) for several minutes under running water. Use lukewarm water if

possible. Remove contact lenses if worn. Get medical attention.

After Skin Contact: Remove contaminated clothing and shoes. Immediately wash with water and soap, rinse thoroughly. If skin irritation continues, consult a doctor.

After Swallowing: Immediately get medical attention. Call a poison center or physician. Rinse out mouth and then drink small amounts of water. Do not induce vomiting as this may be dangerous. Aspiration hazard if swallowed, can enter lungs and cause damage. If vomiting occurs, the head should be kept low to avoid vomit entering the lungs. Maintain an open airway.

Notes to Physician: Treat symptomatically

Section 5: Firefighting Measures

Flash Point:	94 C (201 F)
LEL:	

UEL:

Extinguishing Media:

Alcohol resistant foam Fire-extinguishing powder

Carbon dioxide

Special Hazards Arising from the Substance of Mixture:

Formation of toxic gases is possible during heating or in case of fire. Check flammability in section 2 of this sheet.

Mixture in sealed and heated containers may cause explosion hazard.

Hazardous Combustion Products may include the following:

Carbon oxides. Metal oxide(s). Nitrogen oxides.

Can form explosive vapor-air mixtures

Vapors are heavier than air and may spread along floors. Vapors may travel considerable distance to source of ignition and flash back.

Advice for Firefighters:

Clear fire area of unprotected personnel. Containers that are exposed to intense heat should be cooled with water. Avoid spreading burning liquid with the water used for cooling purposes. Do not enter fire area without protective gear. Fight fire from safe distance or a protected location.

Fire Equipment:

Wear self-contained respiratory protective device. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Section 6: Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Wear protective clothing.

Keep from contacting skin or eyes.

Avoid breathing vapors, mist, or gas.

Ensure adequate ventilation.

Evacuate personnel to safe areas.

If any equipment is necessary, ensure that it is non-sparking and electrically-protected .

Environmental precautions:

Do not allow product to reach sewage system or any water source. In case of seepage into the ground inform responsible authorities Prevent from spreading (e.g. by damming-in or oil barriers). Keep contaminated washing water and dispose of appropriately

Methods and material for containment and cleaning up:

Ensure adequate ventilation

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste.

Do not flush with water or aqueous cleansing agents.

Send for recovery or disposal in suitable receptacles according to local, state and federal regulations .

Section 7: Handling and Storage

Handling:

Apply proper ventilation, possibly combined with local exhaust. Do not eat, smoke or drink during use. For personal protection see Section 8. Keep away from sources of ignition. Keep material out of reach of children. Use only explosion proof equipment. Wash thoroughly after handling.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges by bonding and grounding product containers before and during material transfers.

Keep respiratory protective device available.

Conditions for safe storage, including any incompatibilities:

Storage:

Keep away from sources of ignition - no smoking. Store in a cool, well ventilated place. Keep in original, closed

Specific end use(s): FOR INDUSTRIAL USE ONLY!

Section 8: Exposure Controls/Personal Protection				
Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits	
INERT ADDITIVE I	Not Applicable	Not Applicable	Not Applicable	
Proprietary material	Not Established	Not Established Not Establ		
4-tert-Butylphenol 98-54-4	Not Established	Not Established	Not Established	

Ventilation:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use local exhaust at filling zones and where leakage and dust formation is probable. Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

Personal Protective Equipment/General Protective and Hygienic Measures:

Respiratory Protection:

In outdoor or open areas use (NIOSH/MSHA approved) mechanical filter respirator to remove solid airborne particles of overspray during spray application. In restricted ventilation areas use (NIOSH/MSHA approved) chemical-mechanical filters designed to remove a combination of particulate and gas and vapor. In confined areas use (NIOSH/MSHA approved) airline type respirators or hoods. Respiratory protection may also be necessary in any later manufacturing operations in which the product may become airborne in the form of vapor or dust.

Protective Gloves:

Protective gloves are required for prolonged or repeated contact. Wear resistant gloves such as natural rubber, neoprene, buna N or nitrile. An apron should be worn to avoid skin contact. (Consult your safety equipment supplier.)

Eye Protection:

Avoid contact with eyes. Wear goggles if there is a likelihood of contact with eyes. (Consult your safety equipment supplier.) Eyewash stations and safety showers should be readily available in use and handling areas. Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them.

Body Protection:

Chemically resistance gloves, apron and safety goggles are recommended. Type of protective equipment should be selected based on concentration amount and conditions of use of this material.

Contaminated Gear:

Dispose of in accordance with official regulations.

Section 9: Physical and Chemical Properties

Appearance Liquid Physical State Liquid Odor Typical Solvent Vapor Pressure 0.23 mmHg

Specific Gravity (SG) 1.030

Section 10: Stability and Reactivity

Product Stability:

Product is stable under normal circumstances.

Incompatibilities:

Avoid contact with strong oxidizing agents.

Hazardous Decomposition:

Thermal decomposition may form toxic materials; carbon dioxide, carbon monoxide, etc. Thermal decomposition may form toxic materials; carbon dioxide, carbon monoxide, various hydrocarbons, etc.

Hazardous polymerization will not occur.

Section 11: Toxicological Information			
Mixture Toxicity			
Oral Toxici	y LD50: 22mg/kg		
Component Toxi	city		
98-54-4	4-tert-Butylphenol		
	Oral LD50: 3,250 µL/kg (Rat) Dermal LD50: 2,318 mg/kg (Rabbit)		

Routes of Entry: Ingestion

Target Organs:

Effects of Overexposure

Carcinogenicity:

The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

CAS Number	Description	<u>% Weight</u>	Carcinogen Rating
None			N/A

Section 12: Ecological Information

Environmental Impact Statement/Toxicity:

Aquatic toxicity: No further relevant information available

Persistence and degradability: No further relevant information available

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Other adverse effect: No further relevant information available

Component Ecotoxicity

4-tert-Butylphenol

96 Hr LC50 Pimephales promelas: 4.71 - 5.62 mg/L [flow-through]; 96 Hr LC50 Cyprinus carpio: 6.9 mg/L [static] 48 Hr EC50 Daphnia magna: 3.9 mg/L; 48 Hr EC50 Daphnia magna: 3.4 - 4.5 mg/L [Static] 72 Hr EC50 Desmodesmus subspicatus: 11.2 mg/L

Section 13: Disposal Considerations

Waste treatment methods:

Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal of this product and any by-products must at all times comply with local, state and Federal regulations for hazardous wastes. All entities that store, transport or handle hazardous waste must take the necessary measures to prevent risks of pollution, release into the environment or damage to people and animals.

Contaminated Packaging:

Waste packaging should be recycled. Care should be taken when handling emptied containers that have not been cleaned. Empty containers retain some product residues. Vapor from that residue may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers.

Section 14: Transport Information

Agency	Proper Shipping Name	UN Number	Packing Group	Hazard Class
DOT	Amines, Liquid, Corrosive, n.o.s.	2735`	II	8
IATA	Amines, Liquid, Corrosive, n.o.s.	2735`	II	8
IMDG	Amines, Liquid, Corrosive, n.o.s.	2735	II	8
	NOTE: This product contains a substance that: 1) is regul the definition of toxic to the aquatic environment.	lated as a Marine	Pollutant, or 2) meet	İS

Section 15: Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Prop 65 - Chemicals Known to Cause Developmental Toxicity

- None

Prop 65 - Chemicals Known to Cause Cancer:

- None

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

- None

- U.S. CERCLA/SARA Section 313 Emission Reporting - None
- TSCA (Toxic Substances Control Act)

- None

Country USA

Canada Europe

Regulation

All Components Listed Inventory - United States - Section 8(b) Inventory (TSCA) Yes DSL (Canadian Domestic Substance List) Yes EINECS (European Inventory of Exisitng Commercial Cher No

EU Risk Phrases

Safety Phrase

U.S. - TSCA. - None

U.S. - SARA:

Section 16: Other Information

DISCLAIMER

THE INFORMATION CONTAINED HEREIN WAS RECEIVED FROM OUR RAW MATERIAL SUPPLIERS AND OTHER SOURCES. CONTINENTAL PRODUCTS MAKES NO EXPRESS OR IMPLIED WARRANTIES REGARDING THE ACCURACY OF THE ABOVE INFORMATION AND YOU SHOULD NOT RELY ON IT. YOU SHOULD TEST THIS PRODUCT FOR CHEMICAL COMPOSITION AND CONSULT APPLICABLE SAFETY AND MEDICAL STANDARDS AND PROFESSIONALS RELATED THERETO. CONTINENTAL PRODUCTS DOES NOT WARRANT THE SUITABILITY OF THE PRODUCT FOR ANY APPLICATION BY THE USER, INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE.

Date revised: 2019-02-25 Date Prepared: 3/25/2019 **Reviewer Revision**